



HIGH FLOW SAFETY DRAIN



HIGH FLOW SAFETY DRAIN

CERTIFICATE OF CONFORMITY

SDX HIGH FLOW SAFETY DRAIN

Submerged Suction Outlet
For Single or Multiple Drain Use
For Use on Wall and Floor
No Sump Required

The SDX High Flow Safety Drain is a 10" diameter frame and grate or bulkhead style drain fitting. It includes a back plate and cover that is affixed to a frame, a bulkhead or an existing drain sump. SDX Retro replaces most existing drain covers up to 10" in diameter.

FLOW RATING FLOOR WALL

One SDX or SDX Retro 200 GPM 192 GPM
Square Inches of opening = 43.201 sq. inches
Velocity @ 200 GPM = 1.485 fps

PLACE OF MANUFACTURE:

Paramount Pool & Spa Systems
295 E. Corporate Place
Chandler, AZ 85225 USA
(480) 893-7607

NAME OF THIRD PARTY LABORATORY: IAPMO R&T LAB

TEST RECORD DOCUMENTATION: IAPMO R&T

5001 E. Philadelphia Street
Ontario, CA 91761
(909) 472-4104
Test Report—March 17, 2011

LIFE SPAN: 5 YEARS FROM DATE OF INSTALLATION

COMPLIANT WITH:

- Virginia Graeme Baker Pool and Spa Safety Act
- ASME A112.19.8—2007
- ANSI/APSP - 7
- IAPMO Listed

SDX Model Numbers:

- Concrete XXX-162-2212-XX
- Vinyl XXX-172-2212-XX
- Fiberglass XXX-182-2212-XX
- Retro XXX-192-2212-XX
- Retro Vinyl XXX-159-2212-XX
- Retro Equalizer XXX-157-2212-XX



Install Date _____

Replacement 5 years from installed date _____

NOTE: Suction Safety Standards require that drain grates used to cover sumps must have the suction pipe cut at least 1.5 times the pipe diameter behind the drain cover. There is NO SUMP requirement for SDX because the patented design provides uniform suction regardless of pipe location. If the pipe is too close to the back of the cover, it may restrict water flow to the pump, potentially reducing hydraulic efficiency, but this does not pose a suction safety hazard. This is confirmed by the IAPMO Test Report.

This Product must be installed in accordance with all applicable Federal, State and Local Codes.